CLAIMS

What is claimed is:

1. A phase shifter circuit for imparting a phase shift to a signal applied at an input port such that the phase shifted signal appears at an output port, the circuit comprising:

an input port coupled to receive the input signal;

an output port coupled to provide the phase shifted output signal, the output port coupled to the input port, such coupling between the input port and output port having a characteristic input/output impedance;

a first quadrature port and a second quadrature port, the first and second quadrature ports coupled to one another, such coupling between quadrature ports having a characteristic quadrature port impedance, being different from the input/output port impedance;

a first impedance transformer coupled between the input port and a first one of the quadrature ports, the first impedance transformer transforming the characteristic input/output impedance across the input/output ports to the characteristic quadrature port impedance across the quadrature ports; and

a second impedance transformer coupled between a second one of the quadrature ports and the output port, the second impedance transformer transforming the characteristic quadrature port impedance across the quadrature ports to the characteristic input/output impedance.

2. An apparatus as in Claim 1 wherein the coupling between the input port and output port is provided by a branch line having the desired characteristic input/output impedance.

15

10

20

25

- 3. An apparatus as in Claim 2 wherein the coupling between the quadrature ports is provided by a branch line having the desired characteristic quadrature port impedance.
- 4. An apparatus as in Claim 1 wherein the coupling is provided by coupled lines.
- 5. An apparatus as in Claim 1 wherein the coupling between the quadrature ports is provided by coupled lines.
- 6. An apparatus as in Claim 1 wherein the first impedance transformer is implemented as a one-quarter wavelength section of transmission line.
- 7. An apparatus as in Claim 1 wherein the second impedance transformer is implemented as a one-quarter wavelength section of transmission line.
- 8. An apparatus as in Claim 1 wherein a varactor diode is coupled to at least one quadrature port.
- 9. An apparatus as in Claim 1 wherein a varactor diode is coupled to each of the quadrature ports.
- 10. An apparatus as in Claim 8 wherein an input bias voltage is applied to at least one of the varactor diodes.
- 11. An apparatus as in Claim 9 wherein the voltage of the input bias voltage determines an amount of phase shift imparted by the phase shifter.
- 12. An apparatus as in Claim 1 wherein the characteristic input/output impedance is 50 ohms.

SUP

10

15

,

20

25

- 13. An apparatus as in Claim 1 wherein the characteristic quadrature port impedance is 20 ohms.
- 14. An apparatus as in Claim 1 wherein a Radio Frequency (RF) choke is applied between the bias voltage port and one of the quadrature ports.
 - 15. An apparatus as in Claim 1 wherein the characteristic quadrature port impedance is lower than the characteristic input/output port impedance.